## GRIDDLE



				DIMENSIONS (INCHES)		TEMPERATURES			
MODEL	VOLTAGE	POWER (W)	AMPS	WIDTH	DEPTH	HEIGHT	°C	°F	LBS
EGD-24	208/240 V	4200/5600W	20.2/23.4A	24"	21.7"	12.9"	65°-250°C	150°-480°F	92.92
EGD-36	208/240 V	6300/8400W	30/35A	36"	21.8"	12.9"	65°-250°C	150°-480°F	123.13



**SPECTRUM ELECTRIC GRIDDLES** feature a 1/2" polished steel grill surface with extra tall steel surround wall enclosures. The electric griddles have independent zone controlled heating that allow the operator to use any variety of heat settings from maximum grilling temperature to low warming and holding temperature. Spectrum Electric Griddles are NSF, CUL and UL approved. Warranty and national service program information can be found in the user manual.

- ◆ EGD-24: Two independently controlled heat zones, 24"W x 16-1/2"D grilling surface
- ◆ EGD-36: Three independently controlled heat zones, 36"W x 16-1/2"D grilling surface
- Stainless steel body and catch tray
- ♦ Stainless steel side and rear backsplash for food containment
- ◆ Solid steel plate with a 1/2" thickness on both EGD-24 and EGD-36
- ◆ EGD-24 supplied with a plug and lead (NEMA L6-30P) for quick installation/connection
- Adjustable feet
- ◆ UL listed for compliance with UL-197
- ◆ NSF listed for compliance with NSF-4
- One year warranty

ITEM	DESCRIPTION	UOM
EGD-24	Electric Griddle, 24", 240 Volts, with Plug and Lead	Set
€ FGD-36	Flectric Griddle 36" 240 Volts	Set









## **ELECTRIC COUNTERTOP**

## **GRIDDLE**





