

Blixer® 6



7 Qt.

A SALES FEATURES

Blixer 6 is designed to prepare texture-modified meals with either raw and cooked ingredients in a minimum of time.

B TECHNICAL FEATURES

Blixer 6. 3-phase. Power: 3 HP. Speeds: 1725 and 3450 rpm. 7 Qt. stainless-steel bowl with handle, plus bowl-base, fine-serrated, twin-blade assembly. Totally leakproof lid with scraper arm. 3 – 23 portions (7 oz).

Select your options at the back page, **F** part.

C TECHNICAL DATA

Output power	3 HP
Electrical data	208-240V/60/3
Speeds	1725 and 3450 rpm
Dimensions (WxDxH)	20 13/16" × 14 7/16" × 11"
Rate of recyclability	95%
Net weight	63 lbs
Nema #	L15-20P
Reference	BLIXER 6 - 208-240V/60/3

D

Number of 7 oz portions per service



Amount processed per operation

1 to 8 lbs

E**PRODUCT FEATURES / BENEFITS****MOTOR UNIT**

- Industrial direct-drive (no belt) induction motor designed for intensive use
- Power 3 HP
- Stainless-steel motor shaft
- All-metal motor base
- Magnetic safety system, thermal failsafe
- Speeds 1725 and 3450 rpm

BLIXER® FUNCTION


- 7 Qt. stainless-steel bowl with handle for better grip.
- Bowl-base blade assembly with two high-strength, stainless-steel, fine-serrated blades for homogeneous processing – even for small amounts.
- Central lid opening for adding liquid or solid ingredients during processing.
- High heat and shock-resistant see-through lid to monitor processing from start to finish.
- Leakproof lid and bowl unit with bowl scraper arm and lid wiper.
- All parts are dishwasher-safe and can easily be removed for cleaning.

STANDARD ATTACHMENTS

- 7 Qt. bowl with lid.
- Bowl scraper arm and lid wiper.
- Blade assembly with two fine-serrated, stainless-steel blades and a detachable cap.

STANDARDS

ETL electrical and sanitation Listed/ cETL (Canada)



Blixer® 6

F OPTIONAL ATTACHMENTS

- Fine serrated edge stainless steel "S" blade assembly
Ref. 27169
- 7 Qt. Stainless steel bowl assembly - Ref. 27166

G ELECTRICAL DATA

208-240V/60/3 – delivered with cord and plug.

