Slide Top Bottle Coolers

FBC Series



• FBC-50 • FBC-65 • FBC-79 FBC-95

Item # ____

Standard Features

- Our slide top units are designed with durability and strength along with feature rich standards uncommon in the industry today.
- Refrigeration system is a free flowing air system throughout the box to ensure "ICE COLD" products at all times.
- Heavy duty 18 gauge stainless steel top with anodized aluminum bottle rails.
- Stylish wear resistant black vinyl on steel finish front, sides and back. (S) Models have stainless steel front and sides
- Standard with LED interior lighting to provide full visibility to your bottle and door locks to protect your inventory.
- Heavy duty adjustable bin dividers, epoxy coated.
- Units come with compressor mounted on the right side with service friendly slide out rail system. Drain is located in the back compressor housing.
- (1) Cap catcher Standard.



















Options & Accessories

- Additional dividers
- 220 volts / 50 cycles / 1 phase

Bottle Cooler	Model	Lids	12 Oz. Cans	12 Oz. Bottles	НР	Amps	Cord Length	Cabin W	et Dimens	sions ⊢	Ship (Wt.	ping Cubes)
	FBC-50(S)	2	704	286	1/4	5.9	8'	50-1/2"	26-1/2"	33-3/8"	236	37
	FBC-65(S)	2	890	360	1/3	6.2	8'	65-1/2"	26-1/2"	33-3/8"	275	50.5
	FBC-79(S)	3	1150	547	1/3	6.2	8'	80"	26-1/2"	33-3/8"	315	57
	FBC-95(S)	3	1408	672	1/2	6.5	8'	95"	26-1/2"	33-3/8"	379	69

*Depth does not include 1" bumper

Slide Top Bottle Coolers

FBC Series



Specifications FBC Series

Construction

Heavy duty stainless steel top, 18 gauge. Black vinyl front, sides and back. (S) Models have stainless steel front, sides and back. Interior constructed of heavy duty galvanized steel walls with coved corner galvanized floor.

Lids are heavy duty foamed in place with stainless steel finish. Lids are provided with locks per lid. Unit comes complete with a 1-1/2" Ecomate CFC-Free polyurethane insulation, foamed in place.

Refrigeration System

Self-contained capillary tube system using environmentally friendly (CFC Free) R-134a

refrigerant. Front breathing compressor on right side for built-in applications. Evaporator coil is mounted to interior back panel. Large fan motor and fan blades for greater air flow. Automatic condensate evaporator, drain connection required.

Evaporator condensate has been plumbed to a condensate pan located in the compressor housing. Access for the condensing unit behind the front grill, slides out for easy cleaning and maintenance. Cabinets are designed to maintain temperatures between 28° F to 38° F in the interior cabinet.

Lights

Interior LED light.

Shelving

Adjustable epoxy coated bin dividers provided per unit

Others

Unit is supplied standard with an 8' cord and plug (Nema 5-15p).

Warranty

3 year parts and labor warranty plus 2 additional year compressor warranty. (Continental U.S.A. & Canada only).



