# robot @ coupe°

# Blixer® 5



Blixer 5 is designed to prepare texture-modified meals with either raw and cooked ingrediants in a minimum of time.

**SALES FEATURES** 

# TECHNICAL FEATURES

Blixer 5. 3-phase. Power: 3 HP. Speeds: 1750 and 3450 rpm. 5.5 Qt. stainless-steel bowl with handle, plus bowl-base, fine-serrated, twin-blade assembly. Totally leakproof lid with scraper arm. 3-18 portions (7 oz.).

Select your options at the back page, F part.

C TECHNICAL DATA	
Output power	3 HP
Electrical data	208-240V/60/3
Speeds	1750 and 3450 rpm
Dimensions (WxDxH)	19 3/8" × 14 7/16" × 11"
Rate of recyclability	95%
Net weight	60 lbs
Nema #	L15-20P
Reference	BLIXER 5 - 208-240V/60/3

#### D

Number of 7 oz. portions per service



Amount processed per operation

.075 to 7 lbs

### PRODUCT FEATURES / BENEFITS

# **MOTOR UNIT**

- Industrial direct-drive (no belt) induction motor designed for intensive use
- Power 3 HP
- Stainless-steel motor shaft
- All-metal motor base
- Magnetic safety system, thermal failsafe.
- Speeds 1750 and 3450 rpm

### **BLIXER® FUNCTION**

- 5.5 Qt. stainless-steel bowl with handle for better grip.
- Bowl-base blade assembly with two high-strength, stainlesssteel, fine-serrated blades for homogeneous processing – even for small amounts.
- Central lid opening for adding liquid or solid ingredients during processing.
- High heat and shock-resistant see-through lid to monitor processing from start to finish.
- Leakproof lid and bowl unit with bowl scraper arm and lid wiper.
- All parts are dishwasher-safe and can easily be removed for cleaning.

# STANDARD ATTACHMENTS

- 5.5 Qt. bowl with lid.
- Bowl scraper arm and lid wiper.
- Blade assembly with two fine-serrated, stainless-steel blades and a detachable cap.

### **STANDARDS**

ETL electrical and sanitation Listed/cETL (Canada)



Update: November 2014

Specification sheet

www.robotcoupeusa.com



# Blixer® 5

#### B


# **OPTIONAL ATTACHMENTS**


- Fine serrated edge stainless steel "S" blade assembly Ref. 27155
- Coarse serrated edge stainless steel "S" blade assembly Ref. 27180
- 5.5 Qt. Stainless steel bowl assembly Ref. 27165


C

**ELECTRICAL DATA** 

208-240V/60/3 – delivered with cord and plug.







Update: November 2014