

# Refrigerated Chef Base

## FCBR Series

- **FCBR-52**
- **FCBR-60**
- **FCBR-72**
- **FCBR-84**
- **FCBR-96**



Item # \_\_\_\_\_

## Standard Features

- Our chef bases are designed with durability and strength that you will not find in any other products in its class.
- All stainless steel interior and exterior construction for a clean & safe food environment. Coved corner floor to meet NSF requirements. Drip resistant “V” marine edge protects against spills.
- Drawers: Heavy duty drawer slides, full length recessed drawer handles; accommodate: FCBR-52 (2) 12” x 20” x 4” / (3) 1/6 th x 4” deep pans per drawer. FCBR-60/96 (3) 12” x 20” x 4” deep pans per drawer. FCBR-72 (2) 12” x 20” x 4” deep pans per drawer. FCBR-84 (3) 12” x 20” on right drawer / (2) 12” x 20” x 4” deep pans on the left drawer. (pans sold separately).
- **Forced air inside** to keep products fresher and maintain a constant temperature between **32°F to 41°F** in refrigeration equipment.
- Enhanced digital controller to keep food quality for longer period of time.
- Side breathing refrigeration system for built-in applications.
- **2” Ecomate** CFC-free polyurethane insulation foamed in place for extra strength and energy efficiency. Environmentally friendly with zero ozone depletion (ODP) and zero global warming potential (GWP).
- Equipment mounted on heavy duty **4” castors**.



FCBR-52



FCBR-72



FCBR-96

## Options & Accessories

- 6” Adjustable legs
- 220 volts / 50 cycles / 1 phase



\*Conforms to UL & NSF-7 standards

Chef Base	Model	Drawers	Amps	Cord Length	HP	Volt	NEMA Plug	Cabinet Dimensions			Shipping (Wt. Cubes)
								W	D*	H*	
	<b>FCBR-52</b>	2	3.0	8'	1/3	115	5-15P	53"	32"	25-3/8"	
	<b>FCBR-60</b>	2	-	8'	1/3	115	5-15P	60"	32"	25-3/8"	
	<b>FCBR-72</b>	4	3.8	8'	1/4	115	5-15P	72-1/2"	32"	25-3/8"	
	<b>FCBR-84</b>	4	-	8'	1/4	115	5-15P	84"	32"	25-3/8"	
	<b>FCBR-96</b>	4	-	8'	1/4	115	5-15P	96-5/8"	32"	25-3/8"	

\* Height does not include 4” castors (5” overall)

\*\* Depth does not include 1” bumper

## Specifications

### Construction

Top cover, front and side of heavy duty stainless steel. Galvanized steel rear panel interior made entirely of heavy-duty stainless steel with corners soothed on the floor.

Heavt-duty stainless steel drawers on the outside and inside, sliding guides and positive packaging. Provided with magnetic seal, removable without tools, closing by gravity and with stable opening lock. Door handle integrated throughout.

The unit comes with a 50 mm CFC free polyurethane insulation, foamed on site.

### Refrigeration System

Self-contained capillary tube system using environmentally friendly (CFC free) R-134A refrigerant. Front breathing compressor on left side for built-in applications. Evaporator coil is mounted to interior left side above the compressor. Large fan motor and fan blades for greater air flow.

Cabinets are designed to maintain temperatures between 32°F to 41°F in the interior cabinet.

### Characteristics

Electronic control of digital viewing temp.

### Others

The unit is supplied with a standard 8' electric cable and plug (Nema 5-15p). Equipment on standard 4" wheels.

### Warranty

3 year parts and labor warranty plus 2 additional year compressor warranty. (Continental U.S.A & Canada only).

